



DATA SHEET: BK05/100W/5K, BK05/150W/5K, BK05/200W/5K, BK05/300W/5K & BK05/500W/5K BK05 110/230V LED FLOODLIGHTS



FEATURES

- Prewired 1M flex
- Highly efficient
- Slim Profile
- Die cast construction
- Easy install mounting bracket
- Anti Vandal Polycarbonate Defuser

SPECIFICATION

- BEAM ANGLE: 90°
- COLOUR TEMP: 5000K
- COLOUR EFFECT: PURE WHITE DAYLIGHT
- RATED LIFE: 30,000 HRS
- LED TYPE: SMD2835
- DIMMABLE: NO
- VOLTAGE: 110V/230V AC 50Hz
- IP RATING: IP65
- FINISH: BLACK

CODE	DESCRIPTION	WATTAGE	LUMENS	DIMENSIONS
BK05/100W/5K	100W LED FLOODLIGHT	100W	12,000	221x262x25 (HxWxD)
BK05/150W/5K	150W LED FLOODLIGHT	150W	18,000	256x300x33 (HxWxD)
BK05/200W/5K	200W LED FLOODLIGHT	200W	24,000	283x345x35 (HxWxD)
BK05/300W/5K	300W LED FLOODLIGHT	300W	36,000	330x400x42 (HxWxD)
BK05/500W/5K	500W LED FLOODLIGHT	500W	60,000	535x434x60 (WxHxD)

